



VM-4HC

1:4 HDMI Distribution Amplifier



The VM-4HC is a distribution amplifier for HDMI signals. It reclocks and equalizes the signal and distributes it to four identical outputs.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- EDID Acquisition - Default, single output or all connected outputs (auto-mix).
- HDMI Support - Deep Color, x.v.Color™, up to 7.1 Uncompressed Audio Channels.
- 3D Pass Thru.
- Active Input & Output LED Indicators.
- Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.



VM-4HC

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector.
OUTPUTS:	4 HDMI connectors.
BANDWIDTH:	Supports up to 2.25Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	HDMI and HDCP.
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information.
INDICATOR LEDs:	OUTPUTS 1 to 4 and power LEDs.
POWER SOURCE:	5V DC, 160mA.
DIMENSIONS:	21.5cm x 16.3cm x 4.4cm (8.5" x 6.4" x 1.7") W, D, H.
WEIGHT:	0.6kg (1.32lbs) approx.
ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.

