8" Open-Ceiling Speaker

SOUNDTUBE



#### Specifications: Coming Soon! IPD-HP82-EZ

#### Mounting hardware included

Frequency Response (± 3 dB)	110 Hz - 22 kHz
Frequency Response (±10 dB)	80 Hz - 22 kHz
Max. Power SPL @ 1 M	104.0 dB
Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)	5.0 (Average 100 Hz - 10 kHz) 3.7 (2 kHz)
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)	5.6dB (Average 100 Hz - 10 kHz) 5.7dB (2 kHz)
Total Bi-Amp Power	40 W
Colors	Black/white or custom
Connections	RJ45 ethernet connector
Height (SM = Height)	327.7 mm / 12.9 in
Diameter (SM = Width)	325.9 mm / 12.83 in
Weight	6.35 kg / 14 lbs
Shipping Weight	7.5 kg / 16.5 lbs
Accessories Optional	Beam Clamp (AC-BC-1), Split Loom Tubing (AC-SLT-10),- Hanging Kit (AC-RSEZ-HH-10), Hanging Kit (AC-RSEZ- HH-20), 50' Hanging Kit (AC-RSEZ-HH-50), Forged Eyebolt (AC-FE1), Snap Link (AC-SL-1)

8" Open-Ceiling Speaker

SOUNDTUBE

#### **Description**

Dante®-addressable coaxial pendant speaker incorporates one 8.0 inch (203 mm) high power coaxial driver with BroadBeamHP™ compression driver technology for long throw and smooth directivity. Low latency digital audio, power, and control are delivered to the speaker via standard category cable; connection is made on the other end to the STNet-Switch or other PoE / PoE+ switch. May also be powered via a 24V DC barrel connector for non-PoE installations. Configuration and zoning of the speaker are accomplished via software. Includes hanging hardware with galvanized steel cables and hanging bracket for fast, easy and secure installation. Unit may be hung or mounted directto-conduit via locking cover plate. Enclosure constructed of injection molded ABS with glasber reinforcement for lasting durability in indoor or outdoor applications. Aluminum grille with protective powder coated finish. Unit ships in ecofriendly, recyclable packaging. UL 1480 UEAY, UL 2239 and EN54-24:2008

planned. Included accessories: hanging hardware, weather plug, cover plate, AC-RSEZ-HH-10, and AC-RSEZ-HH-10.

#### Patented SoundTube Technologies

SoundTube and MSE Audio Group constantly develop new technologies that enhance audio product performance. SoundTube innovations are protected by multiple U.S. and international patents, which explicitly cover SoundTube dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect SoundTube resellers and end users.

### Technical Data and Specification Tools

#### **Technical Data**

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are

available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets -Technical information and architectural specs for system engineers  $SoundTubeSPEC^{TM}$  -Proprietary speaker placement software

### Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAA Labs (www.nwaalabs. com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

### Architectural **Specifications**

No specifications currently.

8" Open-Ceiling Speaker

SOUNDTUBE

#### **SoundTube**

8005 W. 110th St. | Suite 208 Overland Park, KS 66210 Phone 9136635600 Fax 8556635600 Toll Free 8556635600 http://soundtube.mseaudio.com All SoundTube products come with a 5-year limited warranty.

8" Open-Ceiling Speaker

SOUNDTUBE

#### **Optional Accessories**

Beam Clamp (AC-BC-1) Hanging Kit (AC-RSEZ-HH-20) Snap Link (AC-SL-1) Split Loom Tubing (AC-SLT-10) 50' Hanging Kit (AC-RSEZ-HH-50)

Hanging Kit (AC-RSEZ-HH-10)

Forged Eyebolt (AC-FE1)