



HDMI 2.0 to DisplayPort 1.2 Converter



HDMI-DP-UHD-II USER MANUAL V2.0

WHAT'S IN THE BOX

- 1 x HDMI-DP-UHD-II
- 1 x 12V Locking PS
- 1 x Mounting Plate
- 1 x User Manual

FEATURES

- Convert HDMI 2.0 (RGB 4:4:4@60Hz) input to DisplayPort 1.2 (SST) output
- HDMI 2.0/1.4 compliant
- DOES NOT support 4:2:0@60Hz
- Supports HDMI input bandwidth up 18 Gbps
- Supports DisplayPort RBR/HBR/HBR2 link rate
- Stereo audio output, 32k – 192k sample rate
- HDCP 2.2/1.4 compliant

SPECIFICATIONS

Functions	HDMI-DP-UHD-II
Input Connector	1 x HDMI 2.0
Output Connector	1 x DP 1.2a (SST)
Audio	Stereo, 32K ~ 192 KHz
Maximum Resolution	4Kx2K@60Hz 4:4:4
Power	DC 12V 1.2A
Weight	356 g
Dimension	69.75x63.5x25 mm
Environment	Operating Temp 0 ~ 45C Operating Humidity 20 ~ 90% Storage Temp – 20 ~ 60C

FRONT VIEW



1. HDMI Input connector
2. LED status indicators
3. Power Jack – 12V DC

REAR VIEW



1. DisplayPort outputs

