

SW-HDMI-4 HDMI 4 Port Switch



Includes IR or RS-232 control

HDMI Cable Locking

Equalizes the inputs for losses in the cable to 65 feet

2.25 Gbps (Gigabits/second) bandwidth

HDMI 1.3, HDCP 1.1, and DVI 1.0 Compliant

Supports High Definition audio – Dolby Digital
TrueHD and DTS-HD

Supports 30/36 bit color depth

The **SW-HDMI-4** is a high performance HDMI Switcher capable of switching and boosting 4 independent HDMI Video+Audio sources to 1 output. Make selections by using the front panel push buttons, using the IR remote control or by RS232 from an external controller.

Since HDMI (and DVI) digital signals have cable distance limitations, the SW-HDMI-4 provides the ability to boost the output signal to drive long HDMI cables to about 50 feet. Furthermore, the unit has built in automatic equalizers on the inputs so that it can handle long input video cables (to 65 feet).

Frequency Bandwidth:	2.25 Gbps (Single Link)
Input Ports:	4 x HDMI Female with locking capability
Output Ports:	1 x HDMI Female with locking capability
Power Supply:	5 vDC @ 1aDC (US/EU Standard, CE/FCC/UL Certified)
Dimensions:	8.1" (206) W x 4.375" (111) D x 1.3" (32) H
Shipping Weight:	1.5 lb (0.70kg)
Product Weight:	0.75 lb (0.35kg)
Enclosure:	Metal
Temperature:	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, non-condensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, non-condensing
MTBF:	90,000 hours (Calculated)
Warranty:	2 Years Parts and Labor

