

What's in the Box?

PART NO.	QTY	DESCRIPTION
HDS-8PS	1	HDMI 8-Port Splitter
Power Supply	1	PS5VDC4A
User Manual	1	

Technical Specifications

VIDEO	
Format	HDMI 1.3b [Deep Color, xvYcc color space supported]
DVI Compliance	Single-link DVI-D 1.1
HDCP Compliance	1.0/1.1
Video Bandwidth	Single-link 340MHz [10.2Gbps]
Resolution	480i,480p,720i,720p,1080i,1080p
Input Interface	(1) HDMI[7.1ch audio & video]
Output Interface	(8) HDMI[7.1ch audio & video]
Connector	Type A[19-pin female]
Maximum Distance	25 ft.
OTHER	
DDC Signal	5 Volts [peak-to-peak], TTL
TDMS Signal	1.2 Volts[peak-to-peak], TTL
Power	External 5VDC4A
Dimensions	17"W x 1.75"H x 5"D
Weight	2 lbs.
Approvals	Device: CE, ROHS Power Supply: C-UL US, CE

© Copyright 2011 Smart-AVI, All Rights Reserved

NOTICE

The information contained in this document is subject to change without notice. Smart-AVI makes no warranty of any kind with regard to this material, including but not limited to, implied warranties of merchantability and fitness for any particular purpose.

Smart-AVI will not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance or use of this material.

No part of this document may be photocopied, reproduced or translated into another language without prior written consent from Smart-AVI.

For more information, visit www.smartavi.com.

Smart-AVI
SMART AUDIO VIDEO INNOVATION

Installation Manual

HDS-8P 8-Port HDMI Splitter



**Connect One HDMI/HDTV
Component to Eight Displays**

Smart-AVI
SMART AUDIO VIDEO INNOVATION

SmartAVI, Inc. / Twitter: smartavi
11651 Vanowen St. North Hollywood, CA 91605
Tel: (818) 503-6200 Fax: (818) 503-6208
<http://www.SmartAVI.com>

www.smartavi.com

Introduction

The HDMI Splitter allows set-top boxes, DVD players, HDMI game console, and other HDTV devices with a HDMI output to be connected to eight HDTV displays.

Supports HDTV's 480i/480p/720i/720p/1080i/1080p & PC's WUXGA/1900x1200 and works with flat panel, plasma screen, projector, switch, splitter, computer video display, HDTV/HDCP, set-top boxes, DTV and DVD.

HDMI can output up to 20 feet from an HDMI device to the HDMI splitter, and then 20 feet from the HDMI splitter to the displays.

Features

- HDMI 1.3c and DVI 1.0 compliant
- HDCP 1.2 compliant
- Wide Frequency Range: 25MHz~225MHz
- Video bandwidth: 6.7GBPS
- Resolution up to 1080p or WUXGA
- Supports CEC (not bypassing)
- Supports Dolby Digital, DTS-HD and Dolby True HD audio
- Easy installation

Applications

- Home Theater Integration
- Restaurants and Bars
- Digital Signage Deployment
- Information Kiosks/Displays
- Film/Recording Studios

Product - Installation Diagram



Installation

1. Turn off the HDMI device and the displays.
2. Connect an HDMI cable from the HDMI output device to the input port on the HDS-8P.
3. Connect the displays to the HDMI outputs on the HDS-8P.
4. Connect the power cord to the HDS-8P.
5. Power on the HDMI device and the displays.

