

Introduction:

The DXE-CAT-RK3 is a 3RU 19" rack mount for the DXE-CAT- RX1 / RX2 / TX1 / TX2 / TX2L products. It can hold up to 16 devices and be easily mounted in the front or rear of the unit due to the low depth. An optional blank plate is available to cover empty slots that are not utilized.



Package Contents:

- 3RU front plate x 1
- Top/bottom plates x 2
- 6/32" Philips Black Flat Countersunk Screws x 10
- 10/32 X 3/4 Round Black Rack Mount Screws x 4

Optional Accessories:

- Blank Plate DXE-CAT-RK3BL

Assembly Instructions:

1. Line up one of the top / bottom plates with the inside of the lip on the 3RU front plate and screw into place using 5 6/32" Philips Black Flat Countersunk Screws. Note the orientation of the plate as the side with the spacer protruding should be facing outward towards the inside lip of the front plate.
2. Repeat step one for the bottom making certain the holes for the DXE-CAT units match up to the top plate.
3. Slide DXE-CAT units into DXE-CAT-RK3 in from the rear, and screw into place using the 4/40" screws supplied with the DXE-CAT unit for the mounting ears. Two will be used for the top and the other 2 for the bottom.
4. If applicable slide Blank Plate DXE-CAT-RK3BL in from the rear and screw into place. The blanks come supplied with 4/40" screws.
5. Insert DXE-CAT-RK3 into rack mount and screw into place using 10/32 X 3/4 Round Black Rack Mount screws. It can be mounted in either orientation that best suites the wiring.
6. Make certain there is proper ventilation above and below the DXE-CAT-RK3. If rack is hot or adequate airflow is not available it is highly suggested to add a fan for proper cooling.

